

CROCODILE

SKIM COAT SMOOTH



CROCODILE

**Great
Covering
Smooth Finish
Weather Resistance**

**Applied Thinly,
Smooth Finish
Like Wallpaper
Dust - Free**



CROCODILE SKIM COAT SMOOTH

Cementitious Smooth Texture Skim Coat

- Thin cementitious plaster; thickness 0.3-3 mm
- Excellent smooth surface finishes
- Great for covering pin holes, cracks, and surface unevenness
- Excellent weathering resistance
- Can be left exposed (white)
- Can be painted over, help reduce paint consumption
- Improved surface durability; no cracking

- For covering cracks in the lightweight concrete, brick blocks or rendered wall -

CROCODILE SKIM COAT SMOOTH

Cementitious Smooth Texture Skim Coat



“Applied thinly, smooth finish like wallpaper, dust-free”



Usage Area


A skim coat for thin cementitious plaster for covering cracks, and surface unevenness. It can be applied to concrete, light weight concrete, blockwork and rendered wall. Excellent weathering resistance and can be used for both interior and exterior. It can reduce paint consumption by 20% (in case of using white skim coat). The product is non-VOC.

Application Instruction

Substrate Preparation

- The substrate must be clean and free from loose particles, dirt, grease and traces of foreign material.
- For loose plaster areas, remove any defective materials and re-plaster the area.
- If the job site is hot or windy, dampen dry surfaces before application.

Application




Mix the CROCODILE SKIM COAT SMOOTH with water at the specified ratio and stir with a mixer at low RPM.



Using a steel trowel, apply Skim Coat evenly to the desired thickness. Thickness for each layer varies from 0.3-3 mm.



If it necessary to increase the thickness of Skim Coat, apply a second coat after the first has set (approx. 10-30 min).



For more smoothness, the surface should be smoothed with sandpaper. Once Skim Coat has dried for 12-24 hours, it can be left exposed or a final coat such as a sealer and decorative paint may be applied.

Proportion of Mixing

- Crocodile Skim Coat Smooth 2.5 kg : water 1 liter or
- Crocodile Skim Coat Smooth 2.5 parts : Water 1 part (by volume)

Estimated Coverage

- 1.25 kg / sq.m. at 1mm thickness

Packing

- 5 kg (bag)
- 25 kg (bag)

Color

- White / Grey



Product Information