

CROCODILE WALL PUTTY



CROCODILE



**Completely
Filled
Easy to Use**

Crack Filling
**Fast
Setting**



CROCODILE WALL PUTTY

Ready - to - Use Acrylic Wall Putty for Filling Crack

- Good adhesion and fast setting
- Easy to apply
- Can be used for interior and exterior
- Free of mercury and lead

- For concrete, plaster, gypsum, red brick, block brick, lightweight brick, fiber cement, and synthetic wood -

CROCODILE WALL PUTTY

Ready-to-Use Acrylic Wall Putty for Filling Crack



“Easy to apply, free of mercury and lead”



Application Instruction

Substrate Preparation

- The substrate must be clean, dust-free and without any traces of oil, laitance, curing compound etc.
- Over plus, seams and rock pockets must be treated prior to application.

Application




1 Apply Crocodile Putty with a wall putty blade or wall putty knife on the cracking wall.



2 Leave to dry, and smoothen the surface by sandpaper



3 For large cracks, grooves or holes, apply in layers by leaving each layer to completely dry before applying another, until filled.



4 Leave to dry for 4 hours before painting



Estimated Coverage

- 0.5-1.5 kg / sq.m.
(5-kg bucket can fill 1x1 cm pre-cast concrete joint with the length of 28.5 m)

Packing

- 5 kg (bucket)
- 1.2 kg (bucket)

Usage Area

Ready-to-use acrylic wall putty for filling cracks, nail heads, seams, or voids. Fast setting, easy to apply, free of mercury and lead. It can be used with various substrates such as concrete, plaster, gypsum, red brick, block brick, lightweight brick, fiber cement, and synthetic wood.

