



Crocodile 9102 W

Acrylic Water-Based Topcoat



An acrylic Water-Based Topcoat that Stain & UV Resistance

Crocodile 9102 W is a siliconized, acrylic-based hybrid, which makes mineral floorings particularly resistant to the most varied oil and water-based stains and greatly increases abrasion resistance. It can be applied in diluted or undiluted form and dries quickly.

Product Features

- Improved abrasion resistance.
- High stain resistance.
- Increased hydrophobicity.
- Easy to clean.
- Easily penetrate the microporous surface and long-term protection.
- UV resistance.
- For both indoors and outdoors.

Application Instruction

Substrate Preparation

- Surfaces should be clean from dust, dirt, oils, grease, curing compounds, other coatings, efflorescence, and laitance before applying Crocodile 9102 W. New concrete should be allowed to cure for at least 28 days before applying Crocodile 9102 W. Substrate moisture level below 4% promotes penetration of product.
- It can be applied by brush, roller, or spray. Apply the product in two coats.
- If the product is used to impregnate porous substrates, we recommend diluting with water of 50% for the priming.
- The second coat may be applied after the first coat dry for 1-3 hours (depending on temperature).
- Treated surfaces should be protected from contamination for 24 hours.
- Surfaces treated with Crocodile 9102 W should be cleaned as soon as they have been exposed to contaminant. Paint is very difficult to remove once it has completely cured.

**Estimated Coverage**

1 liter per 14-15 sq.m. (2 coats) Depending on type and condition of substrate.

Technical Data

Test Method	Evaluation
Solid Content	41-43%
Viscosity	30-130 mPa.s

Caution

Avoid direct acid.

Storage

- Store in a dry and cool place.
- Protect against moisture.
- Shelf life of 1 year, unopened containers.
- The properties required for the intended use must be checked for quality assurance reasons.

Packing

Net weight: 20 liters/pail, 5 liters/gallon, 1 liter/gallon

The information provided is given in good faith, based on current knowledge and Jorakay Corporation's experience with the products when they are properly stored, handled and applied in normal situations and in accordance with the recommendations of Jorakay Corporation. This is useful for information and consulting, but is not legally binding. In particular, it does not exempt the user from testing and verifying the suitability of the product for the desired application and purpose. Jorakay Corporation reserves the right to modifications that improve the product or its application. This version invalidates previous ones.