

Crocodile Skim Coat Sanded Gator

Cementitious Skim Coat



Skim Coat Sanded

Crocodile Skim Coat Sanded Gator is a thin layer 1-6 mm of cementitious plaster which is "Skimmed", e.g. applied very thinly onto interior and exterior of plastered and concrete surfaces. Skim Coats can be applied to concrete, light weight concrete, blockwork and rendered surface.

Product Features

- Improved surface durability; no cracking
- Improved bonding to the base coat
- Covering of pin holes and surface unevenness
- Excellent weathering resistance
- Excellent, smooth or sanded surface finishes

Standard : ASTM C109

Color : White, Grey



Application Instruction

Substrate Preparation

The substrate must be clean and free from loose particles, dirt, grease and traces of foreign material. For loose plaster areas, remove any defective materials and re-plaster the area. If the job site is hot or windy, dampen dry surfaces before application.

Proportion of Mixing

Crocodile Skim Coat Sanded Gator 3.6 kg per water 1 liter

Crocodile Skim Coat Sanded Gator 2.8-3 parts: Water 1 part (by volume)

Estimated Coverage

1.3 kg / 1 sq.m (Thickness 1 mm)

Application

Using a steel trowel, apply Skim Coat evenly to the desired thickness. If it is necessary to increase the thickness of Skim Coat, apply a second coat after the first has set (approx. 15-45 min). Skim Coat Smooth thickness varies from 1-6 mm. The surface should be smoothed with steel trowel. Sanding may be used to obtain an even higher degree of smoothness. Once Skim Coat has dried, a final coat such as a sealer and decorative paint may be applied.

Technical Data

Test Method	Standard	Evaluation
Compressive Strength 28 days	ASTM C109	> 10 MPa
Pull off test @28d	-	> 1 MPa

Caution

- Cement may cause injury to skin or eyes. Use of rubber gloves, dust masks, eye protection, and other safety equipment is recommended.
- If contact with eyes occurs, flush immediately and repeatedly with water, and then contact doctor immediately.
- Avoid contact with skin. Wash thoroughly after handling.
- Keep out of reach of children

Storage

- It should be kept in a dry place and the temperature is not too high to avoid product's degradation.
- Shelf life for 1 year since manufactured date.

Packing

Net weight: 25 kg/bag

The information provided is given in good faith, based on current knowledge and Jorakay Corporation's experience with the products when they are properly stored, handled and applied in normal situations and in accordance with the recommendations of Jorakay Corporation. This is useful for information and consulting, but is not legally binding. In particular, it does not exempt the user from testing and verifying the suitability of the product for the desired application and purpose. Jorakay Corporation reserves the right to modifications that improve the product or its application. This version invalidates previous ones.