



Crocodile Silver Grout

Standard Cement Grout (Unsanded)



For general tiles with USA Standard

Crocodile Silver consists of Portland cement, other chemicals and special colorants, which make the product odorless and prevent the grout from peeling out or shrinkage. The special adhesive in the grout helps with high adhesion and long-lasting. This product is perfect for the joint width that are less than 7 mm, both outdoor and indoor. Because of the very fine powder, this product gives a smooth finished texture when used. To use this product, only mix it with water and apply it to the surface.

Product features

- Good durability and bonding strength without cracking.
- Easy to clean.
- Long lasting.
- Both interior and exterior usage.
- Good for health.
- Joint width 1-7 mm.

USA Standard : ANSI A118.6 (Unsanded)

Color : 39 colors

Installation

Joint width should be between 1-7 mm and depth should not be less than 2/3 of tile thickness. Recommend applying tile grout 48 hours after tile installation.

Preparation

Clean and remove any dirt or contamination remaining in the joints. Make sure the joints are clean and dry before grouting.

Proportion of Mixing

Crocodile Silver 1 kg (per bag) per 0.38 L of water.

Crocodile Silver 3 parts per 1 part of water by volume.



Mixing

- Add the grout into the water and mix well by hand or low speed drill. Allow the grout to slake for 5 minutes, then remix.
- The mix should be stirred intermittently during application.
- Do not add water or grout after this point. If the grout has become too stiff to work, discard it and make a new batch.

Application

1. Fill the joints with well mixed grout, then using a rubber face trowel diagonally across the grout joints.
2. Remove all excess grout with the trowel and leave until curing. Clean tile surfaces with wet sponge and clean cloth.

Curing

Care should be taken within 72 hours to prevent the grout from drying out or dirt by covering the installation with natural kraft paper (Plastic or newspaper sheet should not be used).

Final Clean-Up

10 days after grouting the area should be cleaned to remove any remaining grout from the tile surface. Soaking soap and warm water into the floor and leaving for a while before wiping. It is not recommended to use acids as they cause grout peeling or color alteration

- If necessary, use diluted acid or Crocodile Grout Cleaner. Test in an inconspicuous place first.
- Any glossy coating or special scrubbing should be applied after the grout has completely cured in 30 days. Test in an inconspicuous place first.

Coverage ratio per 1 kilogram (1 bag)

Size of Tiles (in/cm)	Tile Thickness (mm)	Joint width (mm)	Approximate area (sq.m)
1"x1" / 2.5x2.5	4	3	1.1
2"x2" / 5x5	6	3	1.5
		5	0.9
4"x4" / 10x10 (General tile)	6	3	3
		5	1.8
		7	1.3
4"x4" / 10x10 (Cray tile)	10	3	1.8
		5	1
		7	0.7
8"x8" / 20x20	6	3	6
		5	3.6
		7	2.5

Size of Tiles (in/cm)	Tile Thickness (mm)	Joint width (mm)	Approximate area (sq.m)
8"x10" / 20x25	6	3	6.7
		5	4
		7	2.8
12"x12" / 30x30	6	3	9
		5	5.4
		7	3.8
16"x16" / 40x40	8	1	27.2
		2	13.6
		3	9



Information

Density	1.04 g/cm ³
Slake time	5 minutes
Pot life at 23 ± 2 °C	45-60 minutes
Initial setting time	4 hours
Final setting time	5 hours
Waiting time after grouting, keep cement dry at least	48 hours
Time before traffic	72 hours
Joint width	1-7 mm

Remark : Test results obtained from laboratories under controlled conditions may result in testing results that differ from the actual site conditions due to many factors such as temperature, environment, equipment and other.

Technical Data

USA Standard

Test Method by USA Standard (American National Standard Institute)	ANSI A118.6	Standard Requirements A118.6 (Unsanded)	Result
Water absorption 50% RH to immersion	Part 4.4	< 18 %	< 9.5 %
Compressive strength 28 Days	Part 4.5	> 3000 psi (20.7 N/mm ²)	> 3150 psi (21.7 N/mm ²)

Remark : 1 MPa = 1 N/mm² = 10.197 ksc = 145.038 psi

Caution

- Not recommended to use in the area exposed to acid all the time.
- May be harmful to the eyes, skin, or lungs. Wear suitable protective clothing, gloves, and eye/face protection.
- In case of contact with eyes, rinse immediately with water and seek medical advice.
- After contact with skin, wash immediately with water.
- Keep out of reach of children.

Storage

- Lasts up to one year if kept dry and away from heat, in a sealed bag.
- Use within 1 year from the date of manufacturing.



Packing

Net weight : 1 kg / Bag

The information provided is given in good faith, based on current knowledge and Jorakay Corporation's experience with the products when they are properly stored, handled and applied in normal situations and in accordance with the recommendations of Jorakay Corporation. This is useful for information and consulting but is not legally binding. In particular, it does not exempt the user from testing and verifying the suitability of the product for the desired application and purpose. Jorakay Corporation reserves the right to modifications that improve the product or its application. This version invalidates the previous ones.