

# Crocodile 9601 W

## Coating



### Water Repellent & Glossy Finish Enhancement for Wall

Crocodile 9601 W is a stable, organo silicone containing water-based emulsion. When applied to a surface it forms a stable, penetrating water repellent for enhancing a wide variety of porous mineral substrates including concrete, natural and artificial stone and unglazed ceramic tile.

### Product Features

- Enhances the features of the substrate providing a high gloss, wet-look appearance
- Provides excellent dirt pick up and easy to clean.
- Provides excellent water repellency to reduce efflorescence.
- Repels water, reducing penetration while maintaining a consistent appearance.
- Improved UV stability.
- Suitable for interior or exterior decorative stone and concrete projects.

### Application Areas

Mineral-based substrates such as concrete, decorative self-leveling flooring compounds, natural stone and gypsum.

**Color :** White

### Application Instruction

#### Substrate Preparation

- Surfaces should be clean from dust, dirt, oils, grease, curing compounds, other coatings, efflorescence, and laitance.
- New concrete should be allowed to cure for at least 28 days before applying Crocodile 9601 W.
- Substrate moisture level below 4% promotes penetration of product.



### Application

- Shake well before use.
- It can be applied by brush, sponge or roller.
- Multiple coats may be applied wet-on-wet.
- Treated surfaces should be protected from contamination for 24 hours.
- Surfaces treated with Crocodile 9601 W should be cleaned as soon as they have been exposed to contaminant. Paint is very difficult to remove once it has completely cured.
- The water and oil repellency properties will become effective 24 hours after the coating is applied

### Estimated Coverage

1 liter per 8-10 sq.m

### Technical Data

| Test Method   | Evaluation             |
|---------------|------------------------|
| Solid content | approx. 40 % w/w       |
| VOC           | approx. 210 g/L        |
| Density       | 1.08 g/cm <sup>3</sup> |

### Limitation

It is not recommended for below grade applications where hydrostatic pressure can be significant such as swimming pool.

### Caution

- Containers should be closed tightly after use, and smoking should be prohibited in areas where chemicals are handled.
- Store in a cool, well-ventilated place.
- Personal protective equipment (PPE) should be worn when handling chemicals.
- Keep out of reach of children

### Storage

- Store in a dry and cool place.
- Shelf life of 1-year, unopened containers.
- The properties required for the intended use must be checked for quality assurance reasons.

### Packing

Net weight: 20 liters/pail, 5 liters/gallon, 1 liter/gallon

The information provided is given in good faith, based on current knowledge and Jorakay Corporation's experience with the products when they are properly stored, handled and applied in normal situations and in accordance with the recommendations of Jorakay Corporation. This is useful for information and consulting, but is not legally binding. In particular, it does not exempt the user from testing and verifying the suitability of the product for the desired application and purpose. Jorakay Corporation reserves the right to modifications that improve the product or its application. This version invalidates previous ones.