

Gator Self-Leveling Primer



Floor Primer for preparing surface for self-leveling

Gator Self-Leveling Primer is a water-based bonding agent. Its helps to enhance adhesion and reduce air bubble problems prior to applying self-leveling compound. Suitable for using with Crocodile Self-Leveling Gator. It can be used on old and new concrete surfaces.

Product Features

- Enhance adhesion efficiency to the concrete substrate
- Reduce air bubble formation

Application Area

Can be used on old and new concrete surfaces

Color : White

Application

Surface Preparation

The surface must be cleaned without dust, oil stains, curing agent and paint.

Mixing

Mix Gator Self-Leveling Primer 1 part with water 1 part (by volume). Then mix until it becomes a homogeneous mixture.

Application

1. Apply the mixture onto the concrete surface using a nylon brush.
2. After application, protect the surface from dirt and dust.
3. Let it dry completely for at least 3 hours before adjusting with a Crocodile Self-Leveling Gator, but do not leave it for more than 24 hours.
4. Clean the brush or equipment with water.

Estimated Coverage

4-5 sq.m / liter. It depends on the type and condition of the substrate. The exact consumption must be determined by means of a sampling of the work.



Product information

Specific Gravity : 1.01 – 1.05

pH : 9 - 10

Caution

- Product may cause injury to skin or eyes. Use of rubber gloves, dust masks, eye protection, and other safety equipment is recommended.
- If contact with eyes occurs, flush immediately and repeatedly with water, and then contact doctor immediately.
- Avoid contact with skin. Wash thoroughly after handling.
- Keep out of reach of children

Storage

- It should be kept indoors at room temperature and away from source of heat and ignition.
- Shelf life for 1 year from the date of manufacturing when kept in sealed condition.

Packing

Net weight: 1 liter/gallon, 5 liters/gallon

The information provided is given in good faith, based on current knowledge and Jorakay Corporation's experience with the products when they are properly stored, handled and applied in normal situations and in accordance with the recommendations of Jorakay Corporation. This is useful for information and consulting, but is not legally binding. In particular, it does not exempt the user from testing and verifying the suitability of the product for the desired application and purpose. Jorakay Corporation reserves the right to modifications that improve the product or its application. This version invalidates previous ones.