

# Crocodile Admix Mold-O

## Admixture



### Mold Release Oil Base

Crocodile Admix Mold-O is a ready to use, low viscosity oil base release agent for all type of Concrete formwork. It is a light amber liquid that will not stain. It reacts with cement paste at interface of the concrete and formwork to reduce a thin layer coating of film enabling quick, clean and easy striking of formwork. It's suitable for all type of formwork (steel, plastic, woods, or aluminum) and concrete construction.

### Product Features

- Suitable for demolding steel, wood, plastic, and aluminum.
- Easy to demold and clean.
- Does not leave stains on the mold, resulting in a smooth and beautiful concrete surface, and protects steel molds from rust.
- Low viscosity, allowing for coverage of a large area.
- Reduces the occurrence of air bubbles in the concrete surface.

### Application Area

Suitable for application on all types of concrete forms, both for exterior and interior areas.

**Color:** Amber



## Application Instruction

### Substrate Preparation

The surfaces of formwork should be clean and free from oil grease or any contaminant.

### Application

- Applied with a low-pressure spray, sponge mop, roller or brush before erecting the formwork.
- Concrete can be placed soon after application of Crocodile Admix Mold-O.

### Estimated Coverage

The coverage of Crocodile Admix Mold-O is in between 20-60 sq.m./liter

For wood formwork, 20-35 sq.m./liter

For steel and plastic formwork, 1 liter per 35-60 sq.m./liter

### Technical Data

| Property         | Standard Test Method | Result    |
|------------------|----------------------|-----------|
| Specific Gravity | In House             | 0.8 - 0.9 |

### Limitation

Do not add water or other solvents to the product.

### Caution

- Do not inhale or use near open flames.
- For spray application, work in well-ventilated area
- Should be used with protection equipment such as gloves, dust mask and glasses.
- In case of contact with eyes, rinse immediately with water and seek medical advice.
- After contact with skin, wash immediately with water and soap.
- Keep out of reach of children

### Storage

- It should be kept in a dry place and the temperature is not too high to avoid product degradation.
- Use within 1 year from the date of manufacturing.

### Packing

Net weight: 1,000 liter/bucket, 200 liters/drum, 20 liters/pail

The information provided is given in good faith, based on current knowledge and Jorakay Corporation's experience with the products when they are properly stored, handled and applied in normal situations and in accordance with the recommendations of Jorakay Corporation. This is useful for information and consulting, but is not legally binding. In particular, it does not exempt the user from testing and verifying the suitability of the product for the desired application and purpose. Jorakay Corporation reserves the right to modifications that improve the product or its application. This version invalidates previous ones.