

SEE JORAKAY Metallic Loft



Metallic Loft-Style Decorative Paint

SEE Jorakay Metallic loft is a water-based decorative paint that creates a metallic loft pattern. It can be applied immediately after opening the lid. The application can be completed with a single coat without the need for an additional surface coating. This paint is ideal for adding a luxurious finish to interior walls, making it perfect for kitchens, living rooms, children's rooms, or hallway walls. It is odorless with zero VOCs (volatile organic compounds). It can be used on general concrete surfaces, plastered surfaces, cement boards, gypsum boards, and MDF board.

Product Features

- Decorative paint that creates a loft-style metallic finish without needing a top coat
- The surface looks like velvet
- Ready-to-use product, water-based
- Easy to apply, just paint directly onto the desired surface
- Provides excellent adhesion to surfaces
- Odorless with zero VOCs (volatile organic compounds), Safe for the health of users and residents

Color Shade : 32 Shades

Application Area

- General concrete surfaces, plastered surfaces, cement boards, and gypsum boards.



Application Instruction

Substrate Preparation

New surfaces:

- Surfaces should be clean and dry out at least 28 days. Moisture should be not over 14% (measured by a Protimeter).
prepare the surface for painting.
- If the surface has cracks not smooth, recommended to repair cracks or plastering the surface before painting with putty material or suitable surface finishing putty.
- The surface to be painted must be clean, free from dust, loose particles, old paint remnants, and stains.

Old surfaces:

- The surface to be painted must be dry, free from dust, loose particles, old paint remnants, and stains.
- Remove the original paint and deteriorated surfaces. (Do not use a wire brush) if there is dust that cannot be removed completely. Should use a primer
- Area with fungal infection or moss, scrub it with water and brush or high-pressure jet, Apply Crocodile Biocidal Wash and leave it to dry before repainting
- Area with cracks, less than 1 mm width and does not break continuously. Fill it with a *Crocodile Wall Putty*.
- Area with cracks greater than 1 mm width or continuous breakage Fill the putty with *Crocodile Acrylic Seal Plus*

Application:

- In case the surface is not smooth, should be prepared by applying Crocodile skim coat smooth or Crocodile skim coat 102 then sanding to make surface smooth
- Apply 1 coat of *SEE Jorakay Ultimate Primer* (water base). Allow at least 3 hours to dry before applying topcoat
- Apply 1st coat of *SEE Jorakay Metallic Loft* without dilution, by using a roller or trowel. Allow at least 1-2 hours to dry. (Depending on temperature and Humidity)
- Plastering 2nd coat to create patterns by using steel trowel, use a trowel to spread the paint onto the surface in a horizontal back-and-forth motion (freedom cross style). Allow at least 24 hours to dry.

Tools

- Roller, Steel trowel, plastic trowel, and putty trowel.

Tools cleaning

- Clean tools after use with clean water.



Recommendation

- Surfaces should be clean and dry out at least 28 days.
- The product should not be used on wet or high-humidity surfaces. to prevent poor adhesion and paint peeling problems
- In case of rain, let the substrate dry before applying.

Product information

Color	According to catalog
Appearance	Liquid
Film appearance	Metallic (pattern depending on tool)
Density (25°C)	1.1-1.2 g/cm ³
pH	9-10
Viscosity	1400-1900 mPa·s
Estimated coverage	6-8 m ² /l/ 2 coat (It depends on the type and condition of the substrate. The exact consumption must be determined by the means of a sampling of the work)

Caution

- It is recommended to wear safety equipment, such as gloves, dust masks, safety glasses or other safety equipment.
- Use under appropriate conditions with adequate ventilation.
- In the event of eye contact, rinse your eyes with clean water several times immediately and seek medical advice promptly.
- Keep out of reach of children.

Storage

- Store in tightly sealed packaging in a dry place, away from cold air, and avoid exposure to direct sunlight in the storage area.
- Store at temperatures between 5-35°C.
- The shelf life of the product, if not opened for use, can be kept for at least 24 months from the production date.

Packing

- Pack size : 4 L

The information provided is given in good faith, based on current knowledge and Jorakay Corporation's experience with the products when they are properly stored, handled, and applied in normal situations and in accordance with the recommendations of Jorakay Corporation. This is useful for information and consulting but is not legally binding. In particular, it does not exempt the user from testing and verifying the suitability of the product for the desired application and purpose. Jorakay Corporation reserves the right to modifications that improve the product or its application. This version invalidates previous ones.