

Crocodile Silicone MP Gator



Multi-purpose Neutral Silicone Sealant

Crocodile Silicone MP Gator is a neutral (acid-free) silicone adhesive used for waterproof sealing with excellent adhesion to most building surfaces. It is also highly resistant to hot and humid weather conditions due to the absence of acetic acid, ensuring no sour odor during application and preventing damage to metal and copper surfaces. It adheres well to porous concrete and, once cured, remains flexible. It provides excellent adhesion to a variety of surfaces, including glass, tiles, ceramic coatings, glazed tiles, metals, aluminum, steel, zinc, copper, and certain plastics.

Product Features

- Non-shrinking with highly elastic
- No smell of acetic acid during cure time
- Excellent weather ability & durability
- Excellent adhesion to a variety of surfaces.
- Non-corrosive to metals, copper
- Suitable for alkaline substrates such as concrete, mortar, and fibrous cement

Color: White, Clear, Black

Applications

- Joints that move or expand due to temperature changes
- Window glass, door frames with concrete, stainless steel, zinc, plumbing pipes, ceramics
- UPVC windows, wood, aluminum, and metal
- Alkaline surfaces such as concrete



Application Instruction

Surface Preparation

1. The surface must be dry, clean, and free from dust, paint, oil stains, or any other contaminants.
2. The optimal joint width should range from 3 to 12 millimeters, and the depth should be between 5 to 10 millimeters. Ideally, the width should be equal to or greater than the depth of the joint. Foam backing rods can be used to adjust the depth as needed.
3. Adhesive tape should be applied along the joint edges to prevent excess sealant from oozing out during the application process.

Application Instructions

1. Cut the tip of the cartridge and the nozzle at a 45-degree angle, and then attach the nozzle to the cartridge.
2. Using a caulking gun, apply the sealant to the joint, ensuring that it completely fills the void.
3. Smooth the sealant within 10 minutes of application.
4. Clean up any excess sealant using a damp cloth or sponge.
5. Remove the masking tape within 15 to 20 minutes before the sealant fully cures.
6. Allow the sealant to cure for 24 to 48 hours before using.

Coverage: 2.8 m/cartridge (joint width 1x1 cm)

Cleaning: Clean all tools with clean water before the adhesive dries. Remove any remaining hardened adhesive residue by scrubbing or scraping.

Physical Properties

Composition	Silicone
Physical Appearance	Paste
Density	0.98 – 1.50 g/cm ³

Technical Data

Test Method	Evaluation
Tack Free Time (finger touch)	10- 30 min
Tensile Strength	> 1 MPa
Tensile Modulus	
- Clear	0.37 MPa
- White and Black	0.5 MPa
Elongation at Break	
- Clear	> 400%
- White and Black	> 300%
Elastic Recovery Rate	75-85%
Movement Capacity	20%



Test Method	Evaluation
Hardness (Shore A)	
- Clear	20
- White and Black	38

Suggestion

- Not recommended for sealing of aquarium or for long-term use underwater.
- Not suitable for food-grade applications where the joints are likely to come in contact with food.
- Not suitable for the following plastic substrates Polyethylene, Polypropylene, ABS, Acrylic, and Polycarbonate (PC).
- Cannot be painted
- The adhesion can be improved in many cases by pretreatment of the substrate with a primer.

Caution

- Use of rubber gloves, dust masks, eye protection, and other safety equipment is recommended.
- Apply with good ventilation. Do not inhale product.
- In case of contact with eyes, rinse immediately with clean water several times and seek medical advice.
- Keep out of reach of children.
- Do not eat.

Storage

- It should be kept in a dry place, free from moisture, good ventilation and the temperature is not too high to avoid product degradation.
- Shelf life for 12 months from the date of manufacturing when kept in sealed condition.
- Once activated, it not run out remove the nozzle and close the screw cap as before. However, it should be used within 1 month after first opening.

Packing

Net volume : 280 ml./cartridge

The information provided is given in good faith, based on current knowledge and Jorakay Corporation's experience with the products when they are properly stored, handled and applied in normal situations and in accordance with the recommendations of Jorakay Corporation. This is useful for information and consulting, but is not legally binding. In particular, it does not exempt the user from testing and verifying the suitability of the product for the desired application and purpose. Jorakay Corporation reserves the right to modifications that improve the product or its application. This version invalidates previous ones.