



Crocodile A200

Coating



Hybrid Clear Water Base Floor Coating

Crocodile A-200 is a water-based hybrid acrylic polymer for clear coat flooring. It is special formulation for both external and internal area with special properties as a non-yellowing, waterproofing, hard film, excellent adhesion, excellent weatherability and UV resistance, high water resistance, excellent gloss retention and reduced dirt pick-up, can be used for both interior and exterior.

Product Features

- High gloss and long-term durability
- Good adhesion
- Excellent resistance to UV and weather exposure
- Water and dirt pick up resistance
- Excellent water resistant, streak-free and maintains gloss.
- Non-slip surface
- Ready to use
- Water-based formula with a mild odor and environmentally friendly

Application Area

Suitable for sand wash, natural stone, brick stone, terracotta, concrete wall and floor, tile and fiber cement.



Application Instruction

Substrate Preparation

- The surface to be painted must be free from dust and grease oil.
- Remove the original paint and deteriorated surfaces. If there is dust must be removed completely.
- In case of mold and algae, brush and clean with Crocodile Biocidal Wash then leave it dry for 24 hrs. and clean with water before coating with Crocodile A200.

Application Method

Apply two or more coats of Crocodile A200 to the entire surface. The exact number of coats will depend on the porosity of the surface. For highly porous surfaces, additional coats may be necessary. Allow each coat to dry for 3-4 hours before applying the next coat.

Tools

Brush, roller, or spray.

Cleaning

Clean all equipment with clean water immediately after use.

Estimated Coverage

9-11 sq. m./ liter /coat (depending on surface porosity and application method)

Product Information

Composition	: 100% Acrylic hybrid
Color	: White milky liquid
Film appearance	: Clear gloss
pH (25°C)	: 8-9
VOCs Contents (ISO 11890-2)	: <11g/L
Flash point	: Non-flammable
Touch dry (25-30°C)	: 1-2 hours
Recoat dry (25-30°C)	: 3-4 hours
Full cure (25-30°C)	: At least 7 days

Recommendation

- Should be used under appropriate conditions (maximum temperature of substrate: 40°C, maximum relative humidity:85%.)
- Do not apply the product on slippery surfaces, low water absorption materials, or coated surfaces such as ceramic tiles, synthetic tiles, etc.
- Do not apply while the surface is wet and humid.
- Surface moisture should be less than 7% on concrete surface.
- Apply in good ventilation. Do not inhale the product.
- Should not be used in wet and puddle areas.



Caution

- In case of contact with eyes, wash immediately with clean water and seek medical advice.
- Recommend using rubber gloves, dust mask, eyeglasses and personal safety equipment.
- In case of contact with facial skin, clean immediately with soap and clean water.
- Keep out of reach of children.

Storage

- Keep the containers in a dry place and the temperature is not too high to avoid product degradation.
- Shelf life of 1-year, unopened containers.

Packing

Net weight : 5 liters/gallon

The information provided is given in good faith, based on current knowledge and Jorakay Corporation's experience with the products when they are properly stored, handled and applied in normal situations and in accordance with the recommendations of Jorakay Corporation. This is useful for information and consulting but is not legally binding. In particular, it does not exempt the user from testing and verifying the suitability of the product for the desired application and purpose. Jorakay Corporation reserves the right to modifications that improve the product or its application. This version invalidates the previous ones.