



# Crocodile Primer 9801W

## Primer for Old Concrete



### Primer for Old Concrete – Water Based

Crocodile Primer 9801W is formulated from Modified Silicate that designed to improve adhesion on new paint onto old concrete or chalky surfaces. It provides good adhesion and excellent alkali resistance so it is breathable film helps eliminate moisture more effectively. The product is water-based, low odor and environmentally friendly.

### Product features

- Improves the adhesion on new paint onto old concrete or chalky surfaces
- Excellent alkali resistance
- Breathable
- Water-based low odor, Environmentally friendly

### Application Instruction

#### Substrate Preparation

- The surface must be dry and clean without dirt, oil, lubricant, paint, primer, and other stain
- Old concrete surfaces that have been painted or coated with other materials should be scrubbed or scraped to remove the old coating completely.
- Any damage to the surface should be repaired prior to application before coating.
- In case of surface with fungi or algae, clean off by brush, or high water pressure sprayer, and then applied with antifungal and left dry before applying.

#### Application

- Apply the product with brush, roller or spray for 1 layer
- Let it dry least 3 hours before painting

#### Coverage

7-15 m<sup>2</sup> per 1 liter. It depended on type and condition of the substrate.



### Tool

Brush, Roller, or Airless Spray

### Tool cleaning

Clean tools after use by water.

### Suitable surface

- Old concrete or chalky surfaces
- Concrete, Polished cement
- Skim coated walls, Plaster walls, Fiber cement,
- Deteriorated/chalky old concrete
- Drywall, gypsum board and every types of cement surface.

### Topcoat System

- Crocodile Natural Paint (Biosphere Premium, Ecosphere Premium, GrafClean Premium, Stuki Premium)
- Crocodile Color Cement

### Technical Data

Test Method	Standard	Evaluation
Appearance	-	Milky White
Density @25 °C ± 1°C	ISO 2811-1	1.00±0.05 g/cm <sup>3</sup>
pH @25 °C ± 1°C	-	10±1

### Suggestion

- Do not apply on surface in constant contact with water or moisture
- In case of rain, let the substrate dry before applying

### Caution

- Recommend to use rubber glove, dust masks, eye glass and personal safety equipment.
- Apply with good ventilation. Do not inhale product.
- In case of contact with eyes, rinse immediately with water and seek medical advice.
- Keep away from children.

### Storage

- Keep away from direct sunlight.
- The shelf life is approximately 1 year if stored off ground in original, sealed containers.

### Packing

Net weight: 20 liters/bucket, 5 liters/gallon

The information provided is given in good faith, based on current knowledge and Jorakay Corporation's experience with the products when they are properly stored, handled and applied in normal situations and in accordance with the recommendations of Jorakay Corporation. This is useful for information and consulting, but is not legally binding. In particular, it does not exempt the user from testing and verifying the suitability of the product for the desired application and purpose. Jorakay Corporation reserves the right to modifications that improve the product or its application. This version invalidates previous ones.