



Crocodile Admix Plast

Waterproof Admixture



Mortar Plasticizer

Crocodile Admix Plast is a liquid polymer-modified cement admixture for masonry and plastering that reduces surface tension in cement mixes, allowing water to react more completely and evenly with cement and sand, improving workability and smoothness. It contains water-retention agents that slow drying, minimize moisture loss, and help prevent cracking, enabling thinner plaster application that is easy to finish on both walls and ceilings, while enhancing adhesion, durability, and overall plastering performance, saving time and construction costs.

Product Features

- Enhances plastering performance and workability
- Provides higher strength, superior adhesion, and long-term durability
- Improves smoothness and flexibility of plaster, ensuring uniform curing
- Reduces shrinkage, preventing material separation and minimizing pre-plaster cracking

Application area

Used as an admixture for plastering or masonry mortar to enhance workability and improve adhesion performance.

Color: Amber

Application Instruction

Application

Mix Crocodile Admix Plus with water according to the specified mixing ratio.

Combine the diluted solution with cement and sand, then mix thoroughly until well blended.

Estimated Coverage

Crocodile Admix Plast 1-1.5 liters with water 200 liters or

Crocodile Admix Plast (before mixing with water) 100-150 ml per 50 kg cement.



Technical Data

Test Method	Standard	Evaluation
pH	-	8.0-9.5
Specific Gravity	-	1.000-1.005

Limitations

- Do not exceed the recommended mixing ratio, as excessive use may reduce mortar strength.
- The amount of Crocodile Admix Plus can be adjusted according to specific application requirements.
- Plaster consistency and adhesion depend on the characteristics of the sand and other materials used.
- Do not store the admixture beyond its recommended shelf life; older stock should be used first.

Caution

- The product may cause skin irritation; appropriate personal protective equipment such as gloves, dust masks, and safety goggles should be worn during use.
- In case of eye contact, rinse immediately with clean water several times and seek medical attention promptly.
- If the product comes into contact with the face or skin, wash thoroughly with soap and water.
- Keep out of reach of children.

Storage

- It should be kept in a dry place, and the temperature is not too high.
- Use within 1 year from the date of manufacturing.

Packing

Net weight: 200 liters/drum, 20 liters/pail, 5 liters/gallon

The information provided is given in good faith, based on current knowledge and Jorakay Corporation's experience with the products when they are properly stored, handled and applied in normal situations and in accordance with the recommendations of Jorakay Corporation. This is useful for information and consulting, but is not legally binding. In particular, it does not exempt the user from testing and verifying the suitability of the product for the desired application and purpose. Jorakay Corporation reserves the right to modifications that improve the product or its application. This version invalidates previous ones.