

Gator Skim Coat Sanded

Cementitious Skim Coat



Skim Coat Sanded

Gator Skim Coat Sanded is a thin layer 1-6 mm of cementitious plaster which is "Skimmed", e.g. applied very thinly onto interior and exterior of plastered and concrete surfaces. Skim Coats can be applied to concrete, light weight concrete, blockwork and rendered surface.

Product Features

- Improved surface durability; no cracking, no dusting
- Improved bonding
- Covering of pin holes and surface unevenness
- Excellent weathering resistance
- Excellent, smooth or sanded surface finishes

Standard: ASTM C109

Color: White, Grey

The product can contribute to earning points for green building certifications such as LEED, WELL, and TREES.

Application Instruction

Substrate Preparation

- The substrate must be clean and free from loose particles, dirt, grease and traces of foreign material.
- For loose plaster areas, remove any defective materials and re-plaster the area.
- If the job site is hot or windy, dampen dry surfaces before application.



Proportion of Mixing

Gator Skim Coat Sanded 3.6 kg per water 1 liter

Gator Skim Coat Sanded 2.8-3 parts: Water 1 part (by volume)

Estimated Coverage

1.3 kg / 1 sq.m (Thickness 1 mm)

Application

1. Mix Gator Skim Coat Sand with water according to the specified ratio and blend using a low-speed drill mixer.
2. Apply the mixture onto the surface using a steel trowel in a thin, even layer. Each application can achieve a thickness of 1–6 mm.
3. For additional build-up, apply a second layer after the first coat has dried for approximately 15–45 minutes.
4. For an even smoother finish, wet-sand the surface with waterproof sandpaper after the skim coat has dried for 12–24 hours. The finished surface can be left exposed, painted, or further decorated with other materials such as waterproof coatings.

Technical Data

Test Method	Standard	Evaluation
Compressive Strength 28 days	ASTM C109	> 10 MPa
Pull off test @28d	-	> 1 MPa

Caution

- Cement may cause skin irritation; appropriate protective equipment such as gloves, dust masks, and safety goggles should be worn.
- If the product comes into contact with skin, wash thoroughly with soap and water. In case of eye contact, rinse immediately with plenty of clean water several times and seek medical attention promptly.
- Keep out of reach of children.

Storage

- It should be kept in a dry place, and the temperature is not too high
- Shelf life for 1 year since manufactured date in sealed condition.

Packing

Net weight: 25 kg/bag

The information provided is given in good faith, based on current knowledge and Jorakay Corporation's experience with the products when they are properly stored, handled and applied in normal situations and in accordance with the recommendations of Jorakay Corporation. This is useful for information and consulting, but is not legally binding. In particular, it does not exempt the user from testing and verifying the suitability of the product for the desired application and purpose. Jorakay Corporation reserves the right to modifications that improve the product or its application. This version invalidates previous ones.