



# Gator Acrylic Sealant

## Sealant



### **Ready-to-use multipurpose acrylic sealant.**

Gator Acrylic Sealant is a versatile, ready-to-use acrylic sealant. It is odorless, non-corrosive to metals, and dries quickly without sagging. Once dry, it can be painted over and provides strong adhesion to various materials such as wood, concrete, ceramic, tiles, bricks, plaster walls, and synthetic wood.

### **Product Features**

- Flexible
- Crack sealing on concrete or masonry wall
- Fast setting and paintable

### **Application**

Joints in the building between wooden or metal window frames and concrete or brickwork. Joints between stairs and walls, between concrete and ceiling elements, between wall and ceiling, skirting boards or windowsills. The product is suitable for interior applications.

**Color :** White

### **Application Instruction**

1. Ensure all surfaces that will be in contact with the sealant must be clean, dry, and free of dust, dirt, rust, oil and other contaminants.
2. Cut off tip nozzle and cartridge. Screw on nozzle to cartridge.
3. Fit into caulking gun; apply on surface in steady flow.
4. If required, smooth and shape sealant with spatula dipped in mild detergent.
5. Remove excess uncured sealant with a wet cloth. Fully cured excess sealant can be removed by trimming with a sharp knife.



### Estimated Coverage

Cartridge per 3 m length, 1 cm width and 1 cm depth

### Technical Data

Test Method	Standard	Evaluation
Hardness Shore A	ASTM D2240	52
Tack free time	JIS K 6249	$\leq$ 30 min

### Limitations

- Among others not recommended for continuous water emersion and not for PE, PP, Teflon and Bituminous surfaces.
- Not recommend for outdoor application.

### Storage

- Store in dry and cool place below 30 °C
- Use within 12 months from the date of manufacturing.

### Packing

Net weight: 450 grams

The information provided is given in good faith, based on current knowledge and Jorakay Corporation's experience with the products when they are properly stored, handled and applied in normal situations and in accordance with the recommendations of Jorakay Corporation. This is useful for information and consulting, but is not legally binding. In particular, it does not exempt the user from testing and verifying the suitability of the product for the desired application and purpose. Jorakay Corporation reserves the right to modifications that improve the product or its application. This version invalidates previous ones.