

Crocodile Admix Cure

Admixture



Curing Compound

Crocodile Admix Cure is high efficiency concrete curing compound, Sodium Silicate base designed for drying concrete protection which produces a continuous film on the surface of new mortar and concrete. This film slows down water evaporation, which may be excessive in windy or very sunny weather. It is suitable for all general concreting application and of particular benefit for large area concrete surfaces such as floor tops, parking apron, motorways, bridges, etc.

Product Features

- Reduce surface shrinkage and cracking
- Enables cement to hydrate more efficiently
- Provides hard wearing surface and prevents dusting
- Time saving, can be applied immediately after placing concrete

Color: Light Blue

Application Instruction

Substrate Preparation

Dry or moist substrates must be cleaned, load bearing, fine porous and fairly even. If necessary, roughen surface with appropriate device (e.g., abrasive blasting, brush hammering). Any damage should be repaired in advance. The concrete surface must be damp.

Estimated Coverage

6-8 sq.m / liter



Application

- Crocodile Admix Cure must be applied pure onto the surface of the concrete or mortar as soon as it begins to turn matte
- Ensure that surfaces are not running with water prior to application
- If coating is to be applied to the surface, Crocodile Admix Cure should be removed by washing with water after drying
- The product film will disappear in 14-28 days

Technical Data

Test Method	Standard	Evaluation
Specific Gravity	-	1.007-1.095

Caution

- Not suitable for use in acidic environments, as this may cause the material into blue gel.
- Do not inhale.
- For spray application, work in well-ventilated area
- Should be used with protection equipment such as gloves, dust mask and glasses.
- If contact with skin or eyes, clean it with water. If irritation, immediately see a doctor.
- Keep out of reach of children

Storage

- It should be kept in a dry place and the temperature is not too high to avoid product degradation.
- Use within 1 year from the date of manufacturing.

Packing

Net weight: 200 liters/drum, 20 liters/pail

The information provided is given in good faith, based on current knowledge and Jorakay Corporation's experience with the products when they are properly stored, handled and applied in normal situations and in accordance with the recommendations of Jorakay Corporation. This is useful for information and consulting, but is not legally binding. In particular, it does not exempt the user from testing and verifying the suitability of the product for the desired application and purpose. Jorakay Corporation reserves the right to modifications that improve the product or its application. This version invalidates previous ones.