

Crocodile Skim Coat 102

Cementitious Skim Coat



Ready to Use Skim Coat

Crocodile Skim Coat 102 is a ready to use white skim smoothing rendering paste. It's ready to use formula for repairing surface defects in concrete or render. A smooth surface is obtained by eliminating blemishes such as grooves, seams, fine cracks and rock pockets. It's applied for interior and exterior walls, on many kinds of substrate.

Product Features

- Ready to use and easy application
- Perfectly white smooth finish. Thickness 0.2 to 5 mm.
- Can be used to coat over primer and paint
- Excellent trowel ability on application
- Possible to be exposed or painted (with or without primer)
- High compressive and bond strength
- Good weather resistance
- Great for indoor and outdoor

Standard : ASTM C1583

Color : White



Application Instruction

Substrate Preparation

The substrate must be clean, dust-free and without any traces of oil, laitance, curing compound etc. Over plus, seams and rock pockets exceeding 3 mm must be treated prior to application.

Application

Apply small quantities of Crocodile skim Coat 102 with a stainless steel float. Wash the blade to the tool regularly to remove hardened residues. Never return the product to the bucket. Two separate coats must be applied for successful resurfacing (First layer as a primer to fill up all minor defects). Allow 1 hour between each coat. Pre-covering curing time 24 hours (depending on application thickness, covering material and atmospheric conditions).

Estimated Coverage

0.5-1.5 kg / sq.m (thickness 1 mm)

Information

Appearance: White paste

Paste Density: 1.75 g/cm³

Technical Data

Test Method	Standard	Evaluation
Tensile Strength at 28 days	ASTM C1583	> 1 N/mm ²

Remark : 1 MPa = 1 N/mm² , 10.2 ksc, 145.038 psi (Test results are based on laboratory conditions and may vary under actual working environments.)

Caution

- Paste may cause injury to skin or eyes. Use of rubber gloves, dust masks, eye protection, and other safety equipment is recommended.
- If contact with eyes occurs, flush immediately and repeatedly with water, and then contact doctor immediately.
- Avoid contact with skin. Wash thoroughly after handling.
- Keep out of reach of children

Storage

- It should be kept in a dry place and the temperature is not too high to avoid product degradation.
- Use within 1 year from the date of manufacturing

Packing

Net weight: 20 kg/bucket, 5 kg/bucket

The information provided is given in good faith, based on current knowledge and Jorakay Corporation's experience with the products when they are properly stored, handled and applied in normal situations and in accordance with the recommendations of Jorakay Corporation. This is useful for information and consulting, but is not legally binding. In particular, it does not exempt the user from testing and verifying the suitability of the product for the desired application and purpose. Jorakay Corporation reserves the right to modifications that improve the product or its application. This version invalidates previous ones.