# iFix by Jorakay

## Ready-to-Use Tile Grout




**Ready-to-Use Tile Grout for Grout Joint Repair.**

iFix by Jorakay is a ready-to-use grout renovation product specially formulated to refresh, cover, and repair existing grout joints, restoring their appearance to look like new. No need to scrape out existing grout, allowing for fast and convenient application. Simply open and apply with no mixing required. The product provides an easy solution for grout joint renovation and enables the area to be returned to service within 4 hours.

**Product Features**

- Repairs and covers existing grout joints for a like new appearance.
- Convenient and ready to use. No water mixing and no removal of existing grout required.
- Area can be returned to service within 4 hours.*
- Resistant to general cleaning agents.
- Suitable for interior and exterior.
- Suitable for joint widths from 2 to 5 mm and joint depths not exceeding 3 mm.**

*Full drying is achieved within 24 hours.

**If grout collapsing occurs, apply an additional layer of grout.

Color: White

**Pre-Grouting Preparation**

- Joint width should be between 2-5 mm, and joint depth should not exceed 3 mm.
- Inspect the condition of the existing grout joints before application. If the existing grout is loose, deteriorated, or poorly bonded, it should be completely removed prior to grouting.
- Before application, ensure that the grout joints are clean and free from dust, dirt, loose particles, and contaminants that may affect adhesion, such as mold, algae, and grease. Verify that no moisture or standing water remains within the grout joints.
- Where existing grout joints are severely deteriorated or no grout remains, ensure that no moisture or standing water is present beneath the tiles prior to application.
- For interior applications or enclosed spaces, provide adequate ventilation by opening doors and windows or using mechanical ventilation as required to promote efficient drying of the product.


JORAKAY CORPORATION CO., LTD.
10 Krungthepkreetha Road, Thapchang, Saphansung, Bangkok 10250
Tel. 0-2720-1000 (Auto) Fax. 0-2720-1386

**Application**

1.Before application, squeeze the grout tube thoroughly to ensure a uniform consistency. Then remove the cap and cut the nozzle tip.

2.Apply the grout directly into the grout joints, ensuring the joints are completely filled. Tool the surface using a trowel, finger, or other suitable applicator to achieve a smooth and uniform finish.

3.Allow the material to set for approximately 15-20 minutes, then remove any excess grout from the tile surface using a damp cloth or sponge.

4.Allow the product to dry for at least 4 hours before returning the area to service. To ensure proper drying, avoid exposure to water, moisture, or cleaning for at least 24 hours after application.*

*The return to service time is based on proper surface preparation and application in accordance with the product instructions.

**Cleaning After Grouting**

- Remove excess grout from the tile surface with a damp cloth or sponge before the product has fully dried.
- After application, protect the treated area from water, moisture, and cleaning for at least 24 hours to ensure proper drying and performance development.

**Application Limitations**

- Not suitable for swimming pools, ponds, shower areas, bathtub joints, or areas subject to continuous water immersion.
- After application, avoid contact, foot traffic, exposure to water, and moisture for at least 4 hours.
- Do not apply on surfaces with standing water or under high-humidity conditions, as these may adversely affect drying and adhesion performance.
- Should be used under the temperature of 5°C to 35°C.

**Coverage**

The approximate coverage is 30 linear meters per tube (200 ml), based on grout joints 3 mm wide and 3 mm deep.

**Technical Data**

| | |
|---|---|
| Density | 1.60 g/cm$^3$ |
| Waiting time before traffic, keep tile grout dry at least | 4-24 hours* |
| Joint width | 2-5 mm (depth 3 mm) |

*Drying time depends on the surface, thickness, temperature, and humidity.

**Caution**

- May cause irritation to the eyes, skin, or respiratory system. Wear appropriate protective clothing, gloves, and eye/face protection.
- In case of eye contact, rinse immediately with plenty of water and seek medical advice.
- If skin or face contact occurs, wash immediately with soap and water.
- Keep out of reach of children.
- Do not ingest.


JORAKAY CORPORATION CO., LTD.
10 Krungthepkreetha Road, Thapchang, Saphansung, Bangkok 10250
Tel. 0-2720-1000 (Auto) Fax. 0-2720-1386

**Storage Conditions**

- The product should be stored in a shaded, dry, and moisture-free area with good ventilation. Avoid areas with excessively high temperatures, as this may cause product degradation.
- The product has a shelf life of 36 months from the manufacturing date, provided it is stored in a tightly sealed, undamaged, and unopened package.
- If the product is not completely used, tightly close the cap after each use. Please note that the remaining shelf life may be reduced depending on storage conditions.

**Packing**

Net weight: 200 ml tube, packed 12 tubes per box.

**Legal Disclaimer**

The information provided is given in good faith, based on current knowledge and Jorakay Corporation's experience with the products when they are properly stored, handled and applied in normal situations and in accordance with the recommendations of Jorakay Corporation. This is useful for information and consulting but is not legally binding. In particular, it does not exempt the user from testing and verifying the suitability of the product for the desired application and purpose. Jorakay Corporation reserves the right to modifications that improve the product or its application. This version invalidates the previous ones.


JORAKAY CORPORATION CO., LTD.
10 Krungthepkreetha Road, Thapchang, Saphansung, Bangkok 10250
Tel. 0-2720-1000 (Auto) Fax. 0-2720-1386